



DC1500-AB221A  
DC1550-AB321A

*Energy Saving and Noiseless !*

Control  
AB221A / AB321A



Motor  
DC1550

Motor  
DC1500

### TECHNICAL DATA - MOTOR

Maximum speed:	9000 RPM (DC1500) 5000 RPM (DC1550)	Flange dimensions:	80x75 mm
Maximum torque:	3 Nm (DC1500) 8 Nm (DC1550)	Weight:	2.125 kg (DC1500) 3.120 kg (DC1550)
Operating voltage:	230 VAC	Shaft end (cylindrical) with keyway:	Ø14k6
Insulation class:	B	Incremental encoder:	integrated, 512 impulses/ rotation
Protection class:	IP40	Controls:	Series 200 (DC1500) Series 300 (DC1550)
Length:	145.5 mm (DC1500) 185.5 mm (DC1550)		



FRANKL & KIRCHNER GMBH & CO KG  
SCHEFFELSTRASSE 73 · 68723 SCHWETZINGEN  
Tel.: +49 6202 202-0 · Fax: +49 6202 202-115  
E-Mail: info@efka.net · www.efka.net



OF AMERICA INC.  
3715 NORTHCREST ROAD · SUITE 10  
ATLANTA · GEORGIA 30340  
Phone: (770) 457-7006 · Fax: (770) 458-3899  
E-mail: efkaus@bellsouth.net



ELECTRONIC MOTORS SINGAPORE PTE. LTD.  
67, AYER RAJAH CRESCENT #05-03  
SINGAPORE 139950  
Phone: +65 67772459 · Fax: +65 67771048  
E-mail: efkaems@efka.net

